## FUZHOU RAJEYN ELECTRONIC SCI-TEC., LTD.

ADD: No 1 Shiziting Road,Cangshan district,Fuzhou city,Fujian Province P.C.: 350008 Email:info@rajeyn.com Tel:+86-591-83519869

General Information				
Model	RJY-32-G301AD			
Туре	Automatic Concealed Cistern			
Material	Tempered Glass Control Panel		RAJEYN	
Net Weight	1.25kg			
Gross Weight	1.45kg			
Warranty	One Year		W 1 ( )	
<b>Technical Parameters</b>		_		
Working Voltage	DC6V&AC100-240V			
Average static power	<40uA			
Instant dynamic power	<800uA			-
Default Sensor distance	70±7cm cm to Standard White Board (About 55cm to Human Body)			
Adjustable Sensor Range	50-80cm to Standard White Board			
Response Time	3S	88	52.4	
Flush duration	Usage time less than 90s: half flush; Usage time more than 90s: full flush		136. 4	
Flush Volume	2.5L/4.5L OR 3L/6L	230 8 9 8 1 3 9 0 9 8 1 3 9 0 9 8 1 3 9 0 9 8 1 3 9 0 9 8 1 3 9 1 3	184. 8	
Water Pressure	No Requirement (Pneumatic type)	180 130-131	138.5	
Include	Sensor control panel/Water tank/Iron bracket			
Package Information		430 400	T 155. 6	
Inner package	295*190*125mm	430 594 180 180 180 180 180 180 180 180 180 180	308. 3	
Outer package	610*400*270mm			
Quantity per carton	8			
Product Foature				

## **Product Feature**

- 1) Tempered glass design, more durable and elegant.
- 2) Battery mode: LOGO backlight flashes when working. AC power mode: LOGO backlight stays on when working.
- 3) Water saving: Automatic half or full tank flush.
- 4) Standby manual push button can be activated any time.
- 5) Suitable for wall concealed water tank with pneumatic flush valve.