福州锐洁源电子科技有限公司

FUZHOU RAJEYN ELECTRONIC SCI-TEC., LTD.

ADD: No.1 Shiziting Road,Cangshan District, Fuzhou,Fujian,China, 350008 Email: sj.peng@rajeyn.com Skype: rjyjohuang Mob: +86-15060017331

General Information	
Model No.	RJY-11-S201D
Туре	Deck-Mounted Sensor Mixer
Material	Stainless steel with chroming
Mixer	Yes/ for hot and cold water
Net weight	1.5KG
Gross weight	1.6KG
Warranty	One Year
echnical Parameters	
Working power	DC6V
Average static power consumption	<50uA
Instant dynamic power consumption	<2.5W
Working water pressure	7.25-101.5PSI (0.05-0.7MPa)
Sensor distance	4-11.8in (10-30cm)
Error detection time	<0.6 second
Maximum washing period	60 seconds (Default)
Water flow	6.6-7.2L/Min
Mounting diameter	Ø30-40
Environment temperature	34°F-104°F (1~40°C)
Medium temperature	32°F - 149°F (0~65°C)
Inlet diameter	G1/2"
Outlet diameter	G1/2"
Package Information	
Inner package	380*170*113mm
Outer package	525*395*365mm
Quantity per carton	9pcs

Product Feature

- 1) Sensor nearby water spout is automatic on/off. Hands in the sensor range, water comes out. Hands remove from the sensor range, water stops.
- 2) All-in-one design with built-in solenoid valve.
- 3) Adjustable water temperature by manual handle.
- 4) Time Limit: Washing time is set for 60 seconds.
- 5) Low power indication: This may indicate it is time to replace existing batteries with new ones or there is not enough power going to unit.
- 6) Water saving: Water efficient faucet reduces overall water usage without sacrificing water pressure.
- 7) Energy saving: Battery shall last approximately 3000 times/month for 1 year.